



Filter Cartridge Catalog



Make industries
Nature-Friendly



KÖHLER Filter, Inc.
Sale office: 55 west Beaver Creek RD,
Richmond Hill, Unit.68, R5A, 6K2
www.kohlerfilter.com

KÖHLER Filter Cartridge

➤ String Wound Filter Cartridge

Technical Parameter :

- Media material: Polypropylene ,Cotton, Fiber Glass
- Core Material: Polypropylene ,SUS 403,SUS 316
- Precision: 1μm-300μm
- Length: 10'\ 20'\ 30'\ 40"
- Outer diameter: 63-114mm(BB)
- Inner diameter: 30mm/28mm
- Connection: Flat, 222, 226
- Max work Temp: Polypropylene string match with plastic frame: 65 degrees
- Polypropylene string match with galvanized iron: 100 degrees
- Absorbent cotton match with stainless steel skeleton: 120 degrees



➤ Pleated Filter Cartridge

Technical Parameter :

- Filtering accuracy: 0.01μm-70μm
- Flow area: 2':0.6m'
- Material of Film and frame: PP+PP ,
PES+PP , NMO+PP , Hydrophilic PTFE+PP ,
hydrophilic PTFE+PP , PTFE+ECTFE etc.
- The cartridge length: 10 " , 20 " , 30 " , 40 "
- Outer diameter: 70mm
- Connection: Flat, 222, 226
- Seal: Silicone, Buna , EPDM, Viton,



➤ Melt Blown Filter Cartridge

Technical Parameter :

- **Material:** Polypropylene
- **Precision:** 1 μ m-100 μ m
- **Length:** 5", 10", 20" \ 30", 40"
- **Outer diameter:** 63-114mm(BB)
- **Inner diameter:** 30mm/28mm
- **Connection:** Flat, 222, 226, etc.



➤ Activated Carbon Filter Cartridge

Technical Parameter :

- **Material:** Carbon ,fiber contain carbon , carbon string wound
- **Cover:** polyester ;
- **Screen material :** polypropylene
- **Precision:** 5 μ m
- **Size:** 10", 20", 30", 40"
- **Seal:** Buna
- **Option types:** Standard, high adsorption, big fat



➤ Metal Filter Cartridge

Technical Parameter :

- **Material:** SS304, SS316L
- **Precision:** Pleated 1-1000µm, Frit: 0.5-200µm
- **Length:** 10' \ 20", 30", 40"
- **Connection:** Double open with gasket, 222+flat, 222+finned, 226+finned
- **Seal:** Buna, EPDM, Viton, PTFE, Silicone



➤ Titanium Rod Filter Cartridge

Technical Parameter :

- **Material:** Titanium sponge
- **Precision:** 0.22-200µm
- **Size:** 10", 20" \ 30", 40"
- **Connection:** M20, M30, 222, 226 etc.
- **Seal:** Buna, EPDM, Viton, PTFE, Silicone

