

KÖHLER

Spiral E-Coat Ultrafiltration Membrane Element

Model: KM-UF 4033-SEG

➤ **APPLICATION** Electrocoating paints recover in automobile, other industries

PRODUCT DESCRIPTION	Membrane Chemistry:	Polyvinylidene Fluoride (PVDF)		
	Backing Material:	Polyester		
	Permeate Tube:	Unplasticized Polyvinyl Chloride (UPVC)		
	Seal Carrier:	ABS Plastic		
	Brine Seal:	EPDM		
	Construction:	Spiral wound element with fiberglass outerwrap		
SPECIFICATION	Model	Diameter (in) (mm)	Overall Length (in) (mm)	Active Area (ft ²) (m ²)
	SEG-UF-4033	3.9 (99)	33 (838)	61 (5.7)
	Replacements: Sepro PV400-4033-31F Consult Process Engineering Group for specific information.			
OPERATION SPECIFICATIONS	Maximum Inlet Pressure:	65 psi (4.4 bar)		
	Recommended Inlet Pressure:	44-60 psi (3.0-4.1 bar)		
	Recommended Outlet Pressure:	15-40 psi (1.0-2.7 bar)		
	Maximum Operating Temperature:	122° F (50° C)		
	Allowable pH – Continuous Operation:	2.0-10.0		
	Allowable pH – Short Term Cleaning:	2.0-11.5@50°C 30min		
DESIGN PARAMETERS	Feed:	20-24 gpm (76-91 lpm)		
	Permeate Flow on Fresh Lab Paint Baths	0.7-1.0 gpm (2.6-3.8 lpm)		

DIMENSUONS:	Model	A	B	C
	KM-UF 4033-SEG	inches (mm)	inches (mm)	inches (mm)
		33.0 (838)	3.9 (99)	0.625 (15.8)

